

Copperized veil

Code # P25VC

Physical characteristics			
	Unit	Nominal	Tolerance
Mass per unit of area	(g/sqm)	25	± 4%
Weave		Nonwoven, optimally directed	
Thickness	(mm)	0.13	± 15%
Fabric distribution		Polyester	Copper
Weight distribution	(g/sqm)	20	5
Weight distribution	(%)	80	20

Electrical and other characteristics		
Characteristic	Unit	Value
Surface resistivity	(ohms/square)	0.05 - 0.1
Surface conductivity	(Ω)	0.1
EM shielding (single layer)	(dB)	Up to 60
Reflectivity	(%)	70 in IR spektrum (4 - 15 μm)
Air Permeability	(l/m2 s)	1250

Note: Technical information furnished is based on laboratory findings and believed to be correct. No warranties of any kind are made except that the materials supplied are of standard quality. All risk and liabilities arising from handling, storage and use of products, as well as compliance with applicable legal restrictions, rests with the user.



SALES & ORDER PROCESSING
28th of October St No 8A, 37300
Agria, Greece, EU

EU ORDERING INFO
Tel: +302428092210
Email: sales@fibemaxcomposites.com

Head office: Fibremax Ltd
35 Grafton Way, W1T 5DB
London, UK